VISION SHUTTER

EASYVIEW[™]

THE ROLLER SHUTTER WITH A PERMANENT VIEW





EASYVIEW™ ROLLER SHUTTERS

EasyView™ is a strong roller shutter system constructed of an extruded aluminium and a transparent, UV resistant polycarbonate profile, which provides added security and permanent views of the outdoors.

EasyView™ is ideal for providing permanent outside views in a modern and sleek design. The system provides an affordable way of creating that extra room or enclosure, with protection from the elements in both Winter & Summer.

EasyView™ is suitable for various commercial and industrial, shop front, shopping centre grille, cafe & restaurant, counter top and internal separation barrier/ doorway applications, or where both security and visibility are required.







EASYVIEW™ BENEFITS

- Turns open spaces into extra rooms.
- Ideal for shopping centre grilles & cafe applications.
- High quality aluminium & UV resistant polycarb profile.
- Commercial grade double wall extruded profile.
- NEW stronger, larger & clearer 60mm polycarbonate profile with 20% more light & vision.
- NEW high rigidity bottom bar.
- Roll-tight design.
- Suitable for wide shutter widths up to 4400mm.
- High quality powder coated finish.
- Choice of profile colours.
- Fully retractable into an enclosed pelmet.
- Either manual or motorised operation.
- Removable central support guides where required.
- 5 Year Roller Shutter Guarantee.
- Made in Australia.
- Please see "EasyView Care Guide" Leaflet for advice on caring for EasyView Roller Shutters to minimise the occurrence of scuffing and marks during normal use

CONTROL OPTIONS







Spring Loaded With Key Lock With Key Lock (Up To 3.2m Wide)



Crank Handle With Gear Ace (Up To 30Kg)



SolarSmart™ Plus Automation With 12V Motor (Up To 50Kg)



PowerSmart* Control System With 12V Motor (Up To 50Kg) †*



Wall Switch Electric Motor*



With 240V Electric SIMU Hz Motor



Key Switch



Crank Handle With 240V Electric Manual Override



Kev Ring Transmitter With 240V Electric Motor & SIMUDRIVE SD100 Hz Receiver & Control Unit

† When used in conjunction with an assist spring as per CW Products specifications. * Control options must be installed in an indoor environment.

PROFILE COLOUR OPTIONS



TECHNICAL SPECIFICATIONS

Maximum Shutter Width	4400mm
Maximum Shutter Height	3000mm
Profile Slat Covering	36mm Aluminium/60mm Polycarb
Profile Slat Thickness	9.3mm Aluminium/4mm Polycarb
Axle Types	Steel (minimum roll 100mm)
Bottom Bar Dimensions	60mm x 11.5mm
Guide Dimensions	68mm x 25mm/14mm (Heavy Duty Guide)
Paint Finish	High Quality Powder Coat

For more information on EasyView™ Roller Shutters, please contact your nearest dealer, installer or visit www.cwproducts.com.au!

Authorised Dealer:

Note: EasyView is suitable for internal & external use in low to med wind environments. For high wind applications exceeding 25 km/h please contact your CW Products representative. Warranty does not cover wind damage







Exclusively distributed in Australia by CW Products Tel: +61 8 8341 0120 Web: www.cwproducts.com.au