

CYCLONESAFE™

CYCLONE RATED ROLLER SHUTTER

CYCLONE RATED

TESTED BY JAMES COOK UNIVERSITY

CYCLONE RATED UP TO C4

MEETS RELEVANT CYCLONE STANDARDS



PROTECT YOUR HOME! PROTECT YOUR FAMILY!

CycloneSafe™
Roller Shutters

CYCLONESAFE™ ROLLER SHUTTERS CONTROL OPTIONS

With the recent increase in extreme weather and storm conditions across Australia, many Australian home owners and businesses are looking for a better solution for cyclone and storm protection.

It is for this reason that CW Products, (Australia's leading supplier of roller shutters and home automation products) has developed the **CycloneSafe™ Roller Shutter**.

CycloneSafe™ has a Cyclone Rating up to C4 and is compliant with AS/NZS1170.2:2011, which means it can be used in Australian Cyclone Regions including C4 (at a width of 1500mm).

At CW Products we're committed to helping protect Australian families and their homes!



CYCLONESAFE™ BENEFITS

- Cyclone rated in Australian Cyclone Regions up to C4.
- Tested by James Cook University.
- Complies with AS/NZS1170.2:2011 all relevant wind & cyclone standards.
- Commercial grade double wall extruded shutter profile.
- Heavy duty 68mm cyclone guide with locking system.
- Heavy duty steel axle and internal sealed bearings.
- Roll-tight design.
- Suitable for windows up to 2700mm wide (2400mm in NT).
- Suitable for roller doors up to 3000mm wide (2400mm in NT).
- High quality powder coated finish.
- Choice of profile colours.
- Either manual or motorised operation.
- Compatible with SolarSmart™ Plus & PowerSmart™.
- CycloneSafe™ Authentication Plate fitted.
- Made in Australia.

Steel Cable Winder (Up To 50Kg)*

Spring Loaded With Key Lock

SolarSmart™ Plus Automation With 12V Motor (Up To 50Kg)

PowerSmart™ Control System With 12V Motor (Up To 50Kg) †*

Wall Switch With 240V Electric Motor*

Remote Control With 240V Electric SIMU Hz Motor

Key Switch With 240V Electric Motor

Crank Handle With 240V Electric Manual Override Motor

† When used in conjunction with an assist spring as per CW Products specifications.
* Control options must be installed in an indoor environment.

Key Ring Transmitter With 240V Electric Motor & SIMUDRIVE SD100 Hz Receiver & Control Unit

PROFILE COLOUR OPTIONS

Select from our wide range of high quality 36mm Extruded roller shutter profile colours.

	Cream		Black
	Magnolia Cream		Monument
	Clear Beige		Anodised Silver*
	White		Woodland Grey
	Shale Grey	*Not available for pelmets & side frames. Powder coated options available.	

TECHNICAL SPECIFICATIONS

Cyclone Rating	Up To C4
Max Window Shutter Width	Up To 2700mm (2400mm in NT)
Max Roller Door Width	Up To 3000mm (2400mm in NT)
Max Shutter Height	Up To 3000mm
Profile Slat Covering	36mm
Profile Slat Thickness	9.7mm
Axle Types	Octagonal Steel
Bottom Bar Dimensions	55mm x 8.5mm
Guide Dimensions	68mm x 22mm (Heavy Duty Cyclone Guide)
Paint Finish	High Quality Powder Coat

For more information on CycloneSafe™ Roller Shutters, please contact your nearest dealer, installer or visit www.cwproducts.com.au!

Authorised Dealer:



Exclusively distributed in Australia by **CW Products** Tel: +61 8 8341 0120 Web: www.cwproducts.com.au

Illustrations, photos and colours shown in this brochure are for illustrative purposes only. All technical specifications and dimensions are correct at time of printing and may change without notice. For more information please contact your CW Products representative. CycloneSafe and the CycloneSafe logo are trademarks of CW Products. © 2023 CW Products.